
# nf.io: A File System Abstraction for NFV Orchestration


Md. Faizul Bari, **Shihabur R. Chowdhury**, Reaz Ahmed, and Raouf Boutaba David R. Cheriton School of Computer Science University of Waterloo

#### Outline

- What is nf.io?
- Related works
- Why File System abstraction?
- The nf.io File System Abstraction
- Sample Use cases
- System Architecture
- Prototype Implementation
- Work in Progress
- Conclusion



**NFV** Infrastructure




**NFV** Infrastructure


nf.io: A Northbound Interface for NFV Management & Orchestration





NFV Management & Orchestration




**NFV** Infrastructure









- Infrastructure agnostic high level operations
- Resource specific drivers







- Infrastructure agnostic high level operations
- **Resource specific**

#### Related Work

- NFV Platforms
  - Stratos, OpenNF [SIGCOMM '14]
  - o E2 [SOSP '15]
  - OPNFV
- File System Abstraction
  - Linux sysfs, procfs, cgroup
  - yanc [HotNets '13]
- Cloud Orchestrator
  - OpenStack, CloudStack, SaltStack

#### Why File System Abstraction?


- Familiar tools to manage file systems
  - o mkdir, cp, move, rm, rsync, etc.
  - o grep, sed, awk, tail, etc.
    - e.g., instantiate a new VNF
      - mkdir -p /vnfs/user-a/chain-b/ids
- Rich set of file system management operations offered by configuration management tools such as Chef, Puppet, Salt etc.


#### Why File System Abstraction?


- Familiar tools to manage file systems
  - o mkdir, cp, move, rm, rsync, etc.
  - o grep, sed, awk, tail, etc.
    - e.g., instantiate a new VNF
      - mkdir -p /vnfs/user-a/chain-b/ids
- Rich set of file system management operations offered by configuration management tools such as Chef, Puppet, Salt etc.


Rich toolset around File


Systems can be leveraged
if we can translate NFV
operations to File System
Operations


























```
Example:
                  Firewall
                                            Proxy
chns
     chain-alpha
         action
         status
                                  Represents branches of a chain
         strand-1
              fw-alpha
                   fw-alpha -> /vnfs/user-a/nf-types/fw/fw-alpha
next -> /vnfs/user-a/nf-types/proxy/proxy-alpha
              proxy-alpha
                 - proxy-alpha -> /vnfs/user-a/nf-types/proxy/proxy-alpha
              start -> /vnfs/user-a/nf-types/fw/fw-alpha
     chain-beta
```

```
Example:
               Firewall
                                     Proxy
chns
    chain-alpha
        action
        status
        strand-1
                             One directory for each chain component
            fw-alpha
                fw-alpha -> /vnfs/user-a/nf-types/fw/fw-alpha
                next -> /vnfs/user-a/nf-types/proxy/proxy-alpha
            proxy-alpha
                proxy-alpha -> /vnfs/user-a/nf-types/proxy/proxy-alpha
            start -> /vnfs/user-a/nf-types/fw/fw-alpha
    chain-beta
```

```
Example:
               Firewall
                                      Proxy
chns
    chain-alpha
        action
        status
        strand-1
            fw-alpha
                                                                        Symbolic link to VNF instance
                fw-alpha -> /vnfs/user-a/nf-types/fw/fw-alpha
                                                                        Symbolic link to next VNF
                        /vnfs/user-a/nf-types/proxy/proxy-alpha
            proxy-alpha
                proxy-alpha -> /vnfs/user-a/nf-types/proxy/proxy-alpha
            start -> /vnfs/user-a/nf-types/fw/fw-alpha
    chain-beta
```

```
Example:
                     Firewall
                                                     Proxy
chns
     chain-alpha
           action
           status
           strand-1
                 fw-alpha
                      fw-alpha -> /vnfs/user-a/nf-types/fw/fw-alpha
next -> /vnfs/user-a/nf-types/proxy/proxy-alpha
                 proxy-alpha
                 proxy-alpha -> /vnfs/user-a/nf-types/proxy/proxy-alpha


start -> /vnfs/user-a/nf-types/fw/fw-alpha


➤ Symbolic link to the first VNF
     chain-beta
                                                                                           instance in the chain
```


#### Sample Use Cases


- Deploy a VNF instance
  - mkdir nf-types/bro/ids-a
- Configure a VNF instance
  - Migrate a VNF instance to a different machine
     echo '10.0.0.15' > chns/chain-alpha/ fw-alpha/fw-a/machine/ip
- Monitor
  - Total number of packet drops along a chain:
    find -L chns/chain-a pkt\_drops | xargs cat | awk
    '{total += \$1} END {print total}'


# System Architecture











# Work In Progress

- Add support for VNF chains with branches
- Simplify VNF chain representation
- Open vSwitch for end-host data-path
  - Better Programmability
- Add more hypervisor support
  - Xen, KVM
- Integrate with OpenStack

#### Conclusion

- nf.io: A northbound interface for interacting with VNF Management and Orchestration Systems
- nf.io adapts the well known Linux File System abstraction
- **nf.io** allows high level infrastructure agnoistic VNF operations
- Live demo of nf.io:
  - <a href="http://faizulbari.github.io/nf.io/">http://faizulbari.github.io/nf.io/</a> (Link is also in the paper)
  - o Try it out!

# **Questions?**